

Casket Lift


VRC for Commercial Applications

Applications:

- Shaftway
- Enclosure
- Telescopic



Symmetry VRC Advantages:

- Proudly made in the U.S.A. 
- Modular design, no on-site welding required

Shaftway Applications



Single mast casket lift (model 1320) in custom color with fire-rated double swing doors



Single mast casket lift (model 1320) in standard Ivory

Enclosure Applications



Double swing expanded metal gate enclosure (model 1520) in custom color

Telescopic Applications



Telescopic casket lift (model 1520) in custom color

Meeting Your Vertical Conveyance Requirements

For commercial use, Symmetry's Vertical Reciprocating Conveyors (VRCs) are a convenient and safe way to move caskets from floor to floor. **Not rated for passengers or riders**, Symmetry VRCs are designed and manufactured to conform to ASME B20.1.

This brochure is intended for INFORMATIONAL PURPOSES ONLY and SHOULD NOT be used for construction.

Standard Features

- Rated Capacity: 750 to 1,000 lbs.
- Speed: 10-25 fpm
- Lifting Height: Up to 36' (minimum 20" between stops)
- Drive/Suspension: 2:1 Chain Hydraulic
- Stops: Two
- Steel construction with powder-coated finish
- Operation: Automatic for 1320 Single mast
- Operation: Constant pressure for 1520 Telescopic mast
- Controller: Remote
 - NEMA 1
 - Electrical disconnect by others
- TEFC motor
 - 1.15 service factor
 - 240 VAC, 60 Hz, 1 phase
- Modular design, no on-site welding required
- Safety/Warning label package
- Warranty: 5-year limited parts for structural components and 1-year for operational parts

Safety Features

- Overload relief valve
- Pressure gauge
- Emergency stop switch on control stations
- Landing interlocks keep doors closed and locked when platform is not at the landing
- Slack/Broken chain safety switch
- Velocity fuse
- Keyswitch on controls
- Slack/Broken chain safety device
- Manual lowering valve
- 48" tall platform walls on non-loading sides

Optional Features

- Power 208 VAC or 480 VAC
- 3 phase
- Mast guard
- Platform lighting
- Up to five stops
- Single mast (model 1320) or Telescopic mast (model 1520)
- Non-skid platform surface (Black)
- Stationary ramp
- Moving platform audible signal
- Greater capacities available

Clear Platform Sizes

- 36", 42" or 48" width x 96" length

Enter/Exit Configurations

- Straight-Through
- 90°
- Same Side
- 3 Openings

Platform Access/Loading Guards

- Snap chains
- Drop bars

Upper and Lower Landing Access

- Single swing or double swing
 - Fire-rated door
 - Expanded metal gate
- Lift-up gate
- Upper landing (telescopic only)
 - Hatch door
 - Hatch cover



Color Options

Full selection of RAL colors available



Ivory Black White Grey
standard

Colors illustrated may vary due to print or digital technology


Cibães | symmetry



©2020 Bella Elevator LLC. All rights reserved. 4.05.10/20

*Providing Innovative and Creative Designs for
Today's Material Handling Needs*

Symmetry VRC Advantages:

- Made in the U.S.A. 
- Custom designed to your specific application
- Up to a 6,000 lb. capacity
- Factory assembled and tested prior to shipment
- Modular design, no on-site welding required